

Superior Chemistry. Superior Performance.



## 10W-30 Full Synthetic Motor Oil

Printed On: Feb 9, 2014

Formulated to exceed ILSAC GF-4 performance requirements Mag 1 10W-30 Full Synthetic Motor Oil meets MG 4718M Corvette Specs  
Benefits include:

- High temperature film thickness that reduces engine wear
- Includes High Phosphate Retention ZDP for extended wear performance
- Formulated for higher mileage engines

### INSPECTION INFORMATION

### TEST METHOD

### TYPICAL VALUE

Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8556
Viscosity @ 40°C cSt	ASTM D445	66.02
Viscosity @ 100°C cSt	ASTM D445	10.58
Viscosity Index	ASTM D2270	149
Pour Point °C (°F)	ASTM D5950	-42°C (-44°F)
Color	ASTM D 1500	2.5
Cold Cranking Simulator at (°C), cP	ASTM D5293	4654 (-25)
High Temperature / High Shear Vis at 100°C, cP	ASTM D 6616	7.83
High Temperature / High Shear Vis at 150°C, cP	ASTM D5481	3.32
Noack Volatility, % loss	ASTM D 6375	7.4
Calcium, wt. %	ASTM D 5185	0.214
Zinc, wt. %	ASTM D 5185	0.085
Phosphorus, wt. %	ASTM D 5185	0.077
Sulfur, wt. %	ASTM D 4951	0.332
Boron, wt. %	ASTM D 5185	0.023
Molybdenum, wt. %	ASTM D 5185	0.0079
Sulfated Ash, wt. %	ASTM D 874	0.92
Nitrogen, wt. %	ASTM D 4629	0.102
Pumping Viscosity at (°C), cP	ASTM D4684	14,306 (-30)
Shear Stability	ASTM D 6278	9.98
Foam Seq. I (Tendency/Stability), mL	ASTM D 892 (Opt. A)	0/0
Foam Seq. II (Tendency/Stability), mL	ASTM D 892 (Opt. A)	0/0
Foam Seq. III (Tendency/Stability), mL	ASTM D 892 (Opt. A)	0/0
High Temperature Foaming, static foam	ASTM D 6082 (Opt A)	0/0
Gravity, °API	ASTM D287	33.88
TBN, mgKOH/g	ASTM D 2896	7.9

Superior Chemistry. Superior Performance.



## CLAIMS INFORMATION

Printed On: Feb 9, 2014

API SN	Approved
API SM	Meets Requirements
API SL	Meets Requirements
Chrysler MS-6395	Meets Requirements
ILSAC GF-5	Approved
ILSAC GF-4	Meets Requirements
GM 6094M	Meets Requirements
GM 4718M	Meets Requirements
Ford ESE-M2C153-E	Meets Requirements

Ford ESE-M2C153-E