

Superior Chemistry. Superior Performance.



## 5W-20 Synthetic Blend Motor Oil

Printed On: Feb 9, 2014

Formulated to exceed ILSAC GF-4 performance requirements, Mag 1 5W-20 Synthetic Blend Motor Oil meets all Ford, Honda, Chrysler, and Toyota 5W-20 specifications

Benefits include:

- Formulated with High Phosphate Retention ZDP for extended wear performance
- Improved Fuel Economy

### INSPECTION INFORMATION

### TEST METHOD

### TYPICAL VALUE

Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8592
Viscosity @ 40°C cSt	ASTM D445	47.17
Viscosity @ 100°C cSt	ASTM D445	8.27
Viscosity Index	ASTM D2270	151
Pour Point °C (°F)	ASTM D5950	-30°C (-22°F)
Color	ASTM D 1500	2
Cold Cranking Simulator at (°C), cP	ASTM D5293	5710 (-30)
High Temperature / High Shear Vis at 100°C, cP	ASTM D 6616	6.02
High Temperature / High Shear Vis at 150°C, cP	ASTM D5481	2.79
Noack Volatility, % loss	ASTM D 6375	14.2
Calcium, wt. %	ASTM D 5185	0.25
Zinc, wt. %	ASTM D 5185	0.098
Phosphorus, wt. %	ASTM D 5185	0.077
Sulfur, wt. %	ASTM D 4951	0.298
Boron, wt. %	ASTM D 5185	0.018
Sulfated Ash, wt. %	ASTM D 874	0.92
Nitrogen, wt. %	ASTM D 4629	0.102
Pumping Viscosity at (°C), cP	ASTM D4684	15,980 (-35)
Shear Stability	ASTM D 6278	7.8
Foam Seq. I (Tendency/Stability), mL	ASTM D 892 (Opt. A)	0/0
Foam Seq. II (Tendency/Stability), mL	ASTM D 892 (Opt. A)	0/0
Foam Seq. III (Tendency/Stability), mL	ASTM D 892 (Opt. A)	0/0
High Temperature Foaming, static foam	ASTM D 6082 (Opt A)	50/0
Gravity, °API	ASTM D287	33.19
TBN, mgKOH/g	ASTM D 2896	8.5

Superior Chemistry. Superior Performance.



## CLAIMS INFORMATION

Printed On: Feb 9, 2014

API SN	Approved
API SM	Meets Requirements
API SL	Meets Requirements
Chrysler MS-6395	Meets Requirements
ILSAC GF-5	Approved
ILSAC GF-4	Meets Requirements
M2C945-A, M2C930-A	Meets Requirements
GM 6094M	Meets Requirements