

Superior Chemistry. Superior Performance.



5W-30 Full Synthetic Motor Oil C-3/SM

Printed On: Feb 9, 2014

INSPECTION INFORMATION

Specific Gravity @ 60°F (15.6°C)
Viscosity @ 40°C cSt
Viscosity @ 100°C cSt
Viscosity Index
Pour Point °C (°F)
Color
Cold Cranking Simulator at (°C), cP
High Temperature / High Shear Vis at 150°C, cP
Pumping Viscosity at (°C), cP
Gravity, °API
TBN,mgKOH/g

TEST METHOD

ASTM D4052
ASTM D445
ASTM D445
ASTM D2270
ASTM D5950
ASTM D 1500
ASTM D5293
ASTM D5481
ASTM D4684
ASTM D287

TYPICAL VALUE

0.8517
70.01
12.02
170
-45°C (-49°F)
2
5627 (-30)
3.56
22,234 (-35)
34.64
8

CLAIMS INFORMATION

API SM
Chrysler MS-6395
API CF
ACEA C3-08
ACEA A3/B3-08 and A3/B4-08
MB p229.31 / p229.51
BMW LL-04
VW 502 00 / 505 00

Approved
Meets Requirements
Meets Requirements
Meets Requirements
Meets Requirements
Meets Requirements
Meets Requirements
Meets Requirements