



## Typical Chemical Characteristics

---

### Product:

**Anax 4000** "Fully Synthetic" SAE 10W-60, 5W-50 & 5W-40 (ex HT-4000)

### Description:

EN:  
Fully synthetic engine oil, which is developed for racing or sport car's engines that require extended lubrication in all conditions and endurance in mechanical exhaustion. It is formulated with Full SAPS technology and it is absolute suitable for modified engines.

EL:  
Πλήρες συνθετικό λιπαντικό με τεχνολογία Full SAPS. Είναι ειδικά σχεδιασμένο για να παρέχει τέλεια προστασία και μακρά διάρκεια ακόμα και σε αντίξοες μηχανικές συνθήκες σε αγωνιστικούς αλλά και για βελτιωμένους κινητήρες.

BG:  
Състезателно, пълно синтетично моторно масло за автомобили, при които е необходимо продължително смазване при всякакви условия и устойчивост на механично износване. Специално проектирано за доработени двигатели на състезателни или рали автомобили.

FR:  
Huile moteur entièrement synthétique pour des applications dans toutes les conditions de course. Spécialement conçu pour les moteurs réglés de voitures de rallye ou course.

**Disclaimer:** The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although RS200 motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and RS200 motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.



## Typical Chemical Characteristics

### Characteristics:

Property	Method	Unit	10W-60	5W-50	5W-40
Specific Gravity 15°C	ASTM D 1298	kg/L	0,878	0,881	0,879
Viscosity at 100°C	ASTM D 445	cSt	21,9 - 26,1	16,3 - 21,9	12,5 - 16,3
Viscosity Index	-	-	>130	>130	>130
Pour Point	ASTM D 97	°C	<25	<30	<30
Flash Point	ASTM D 92	°C	>210	>210	>210
Total Base Number	ASTM D 2896	mgKOH/g	>6,5	>6,5	>6,5
Color	-	-	Crystal gold	Crystal gold	Crystal gold
Cold Cranking Simulator	ASTM D 5293	mPa-s	<3500 @ -20°C	<3500 @ -25°C	<3500 @ -25°C

### Specifications:

10W-60 & 5W-50: API: SM/SL/CF

5W-40: API: SM/SL/CF & ACEA: A3/B3 & A3/B4

**Disclaimer:** The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although RS200 motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and RS200 motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.