

Superior Chemistry. Superior Performance.



Antiwear R&O ISO 22 Hydraulic Fluid

Printed On: Feb 10, 2014

INSPECTION INFORMATION

Specific Gravity @ 60°F (15.6°C)
Viscosity @ 40°C cSt
Viscosity @ 100°C cSt
Pour Point °C (°F)
Viscosity Index
Color
Zinc, wt. %
Phosphorus, wt. %
Calcium, wt. %
Sulfur, wt. %
Gravity, °API
Oxidation Hours

TEST METHOD

ASTM D4052
ASTM D445
ASTM D445
ASTM D5950
ASTM D2270
ASTM D 1500
ASTM D 5185
ASTM D 5185
ASTM D 5185
ASTM D 4951
ASTM D287
ASTM D943

TYPICAL VALUE

0.8576
21.82
4.36
-36°C (-33°F)
107
0.5
0.041
0.033
0.003
0.065
33.50
5000

CLAIMS INFORMATION

ASTM D6158
Parker Denison HF-0, HF-1
Parker Denison HF-2
Vickers I-286-S, M-2950-S
US Steel 127, 136
DIN 51524, Part 1,2,3
General Motors LS-2
JCMAS HK
Bosch Rexroth

Meets Requirements
Suitable for Use
Suitable for Use
Suitable for Use
Suitable for Use
Suitable for Use
Suitable for Use
Suitable for Use
Suitable for Use