



Printed On: Feb 10, 2014

Benefits of Mag 1 Antiwear R&O ISO 32 Hydraulic Fluid include:

- Exceptional protection against wear from contaminants and higher operating temperatures and pressures ensures longer equipment life
- Maintains viscosity, even under higher operating temperatures, and has sufficient reserve of key additives, resulting in longer fluid life and reduced operating costs
- Reduced foaming ensures smooth, efficient operation and proper lubrication of all parts in the system

## INSPECTION INFORMATION

Specific Gravity @ 60°F (15.6°C)

Viscosity @ 40°C cSt

Viscosity @ 100°C cSt

Pour Point °C (°F)

Viscosity Index

Color

Zinc, wt. %

Phosphorus, wt. %

Calcium, wt. %

Sulfur, wt. %

Gravity, °API

Oxidation Hours

## TEST METHOD

ASTM D4052

ASTM D445

ASTM D445

ASTM D5950

ASTM D2270

ASTM D 1500

ASTM D 5185

ASTM D 5185

ASTM D 5185

ASTM D 4951

ASTM D287

ASTM D943

## TYPICAL VALUE

0.8631

32.11

5.55

-33°C (-27°F)

110

0.5

0.041

0.033

0.003

0.065

32.44

5000

## CLAIMS INFORMATION

ASTM D6158

Cincinnati/MAG IAS P-68

Parker Denison HF-0, HF-1

Parker Denison HF-2

Vickers I-286-S, M-2950-S

US Steel 127, 136

DIN 51524, Part 1,2,3

General Motors LS-2

JCMAS HK

Bosch Rexroth

Meets Requirements

Suitable for Use

Suitable for Use

Suitable for Use

Suitable for Use

Suitable for Use

Suitable for Use

Suitable for Use

Suitable for Use

Suitable for Use