

Superior Chemistry. Superior Performance.



Full Synthetic Multi-Vehicle Automatic Transmission Fluid

Printed On: Feb 10, 2014

INSPECTION INFORMATION

Specific Gravity @ 60°F (15.6°C)
Viscosity @ 40°C cSt
Viscosity @ 100°C cSt
Pour Point °C (°F)
Viscosity Index
Color
Rust Protection
Gravity, °API
Brookfield Viscosity at -40°C, cP
Copper Strip Corrosion (3 hrs@100°C)

TEST METHOD

ASTM D4052
ASTM D445
ASTM D445
ASTM D5950
ASTM D2270
ASTM D 1500
ASTM D 665A
ASTM D287
ASTM D2983
ASTM D 130

TYPICAL VALUE

0.8516
33.64
7.41
-51°C (-60°F)
196
Red
Pass
34.66
10,300
1B

Superior Chemistry. Superior Performance.



CLAIMS INFORMATION

Printed On: Feb 10, 2014

Allison C-4	Meet Requirements
Audi G 052 025, 052 162, 055 025	Suitable for Use
BMW 7045E, LA2634, LT71141	Suitable for Use
Dexron III, Dexron II, Dexron	Suitable for Use
Hyundai/Kia SP-II and SP-III	Suitable for Use
Idemitsu K17	Suitable for Use
JWS 3309	Suitable for Use
M315-2004 JASO 1A	Meet Requirements
MAN 339 Type Z1, V1	Suitable for Use
MAN 339 Type V2	Suitable for Use
Mazda ATF M-III, MV	Suitable for Use
NAG-1	Suitable for Use
MB236.1,2,5,6,7,9, 10, 11	Suitable for Use
Mercon V (XT-5-QM,XT-5-DM)	Meet Requirements
Mercon, Ford ESP-M2C166-H	Suitable for Use
Mitsubishi Diamond SP-II, SP-III, J2	Suitable for Use
Nissan Matic-D, J, K, 402	Suitable for Use
Shell 3403, LA2634, Texaco 7045-E, ETL-8072B	Suitable for Use
Subaru ATF, ATF-HP	Suitable for Use
Toyota T-III, T-IV, WS, Ford XT8QAW	Suitable for Use
Voith 55.6335 (G607)	Suitable for Use
Volvo Passenger Car (4 – 6 sp), Volvo 97340, 97341	Suitable for Use
VW G 052 025, 162, 099, 055 025	Suitable for Use
ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C	Suitable for Use
ZF TE-ML 14B	Suitable for Use

MAN 339 Type Z1, V1