

Superior Chemistry. Superior Performance.



Multi-Vehicle Transmission Fluid

Printed On: Feb 10, 2014

Benefits of Mag 1 Multi-Vehicle ATF include:

- Excellent high and low temperature protection
- Stable friction properties for smooth and consistent shifting
- Excellent sheer stability
- Suitable for use in Chrysler automatic transmissions requiring the 3 and 4 Chrysler automatic transmission fluids

INSPECTION INFORMATION

Specific Gravity @ 60°F (15.6°C)
Viscosity @ 40°C cSt
Viscosity @ 100°C cSt
Pour Point °C (°F)
Viscosity Index
Color
Gravity, °API
Brookfield Viscosity at -40°C, cP

TEST METHOD

ASTM D4052
ASTM D445
ASTM D445
ASTM D5950
ASTM D2270
ASTM D 1500
ASTM D287
ASTM D2983

TYPICAL VALUE

0.8601
35.43
7.56
-51°C (-60°F)
189
Red
33.02
11,300

Superior Chemistry. Superior Performance.



CLAIMS INFORMATION

Printed On: Feb 10, 2014

| | |
|--|--------------------|
| Allison C-4 | Approved |
| Audi G 052 025, 052 162, 055 025 | Suitable for Use |
| BMW 7045E, LA2634, LT71141 | Suitable for Use |
| Dexron III, Dexron II, Dexron | Suitable for Use |
| Honda DW-1, Z-1 | Suitable for Use |
| Hyundai/Kia SP-II and SP-III | Suitable for Use |
| Hyundai SP-IV | Suitable for Use |
| Idemitsu K17 | Suitable for Use |
| JWS 3309 | Suitable for Use |
| M315-2004 JASO 1A | Approved |
| MAN 339 Type Z1, V1 | Meets Requirements |
| MAN 339 Type Z2 | Meets Requirements |
| Mazda ATF M-III, MV | Suitable for Use |
| MB236.1,2,5,6,7,9, 10, 11 | Suitable for Use |
| Mercon V (XT-5-QM,XT-5-DM) | Approved |
| Mercon, Ford ESP-M2C166-H | Suitable for Use |
| Mitsubishi Diamond SP-II, SP-III, J2 | Suitable for Use |
| Nissan Matic-D, J, K, 402 | Suitable for Use |
| Shell 3403, LA2634, Texaco 7045-E, ETL-8072B | Suitable for Use |
| Subaru ATF, ATF-HP | Suitable for Use |
| Toyota T-III, T-IV, WS, Ford XT8QAW | Suitable for Use |
| Voith 55.6335 (G607) | Suitable for Use |
| Volvo Passenger Car (4 – 6 sp), Volvo 97340, 97341 | Suitable for Use |
| VW G 052 025, 162, 099, 055 025 | Suitable for Use |
| ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C | Suitable for Use |
| ZF TE-ML 14B | Meets Requirements |

JWS 3309