



Typical Chemical Characteristics

Product:

RR 4T “Fully Synthetic” SAE 5W-40

Description:

It belongs to the latest technology formula of fully synthetic lubricant absolutely suitable for race conditions. Includes special additives ensuring stability and excellent behaviour under hard drive conditions gadding in the same time longer oil change spaces.

Characteristics:

| Property | Method | Unit | Result |
|-------------------------|-------------|-------|---------------|
| Specific Gravity 15°C | ASTM D 1298 | kg/L | 0,879 |
| Viscosity at 100°C | ASTM D 445 | cSt | 12,5 – 16,3 |
| Viscosity Index | - | - | >130 |
| Pour Point | ASTM D 97 | °C | <-20 |
| Flash Point | ASTM D 92 | °C | >200 |
| Color | - | - | Crystal gold |
| Cold Cranking Simulator | ASTM D 5293 | mPa-s | <3500 @ -25°C |

Specifications:

API: SL
JASO MA/MA 2

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although RS200 motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and RS200 motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.