



Typical Chemical Characteristics

Product:

SS 2T “Semi Synthetic”

Description:

Semi Synthetic lubricant from high quality first materials for use in two stroke engines only. It provides less smoke, high lubrication, no residues and combustion chamber's purity. The suggested analogy is 50:1 with fuel. It is also recommended for racing use.

Characteristics:

Property	Method	Unit	Result
Specific Gravity 15°C	ASTM D 1298	kg/L	0,88
Viscosity at 100°C	ASTM D 445	cSt	7,5
ISO EGD 3h Detergency	Engine Test	-	≥ 125
ISO EGD 3h Varnish Index	Engine Test	-	≥ 95
Viscosity Index	-	-	> 95
TISI Detergency	Engine Test	-	≥ 48

Specifications:

API: TC
 JASO FB/FC
 ISO-L-EGD/EGC

Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.