



Typical Chemical Characteristics

Product:

Speed Oil S3.40 & S3.30

Description:

Special mineral lubricant formulated from high quality materials and from special developed additives for truck's diesel engines which haul heavy loads and operate under exhausted conditions.

Characteristics:

Property	Method	Unit	S3.40	S3.30
Specific Gravity 15°C	ASTM D 1298	kg/L	0,89	0,89
Viscosity at 100°C	ASTM D 445	cSt	12,5 - 16,3	9,3 - 12,5
Viscosity Index	-	-	>105	>105
Pour Point	ASTM D 97	°C	<12	<12
Flash Point	ASTM D 92	°C	>210	>210
Color	-	-	Crystal gold	Crystal gold

Specifications:

API: CF/SF
 ACEA: E2
 MB p228.0, MAN 270/271, BELARUS,
 CATERPILLAR TO-2

Disclaimer: The data given here is based on typical chemical characteristics of the current product and could change without any verbal or written notification. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations.